

FULLY AUTO DIGITAL CHARGER



MHFamily :MH-1210A/MH-1220A/MH-1230A

FEATURES

- 1 . Car Engine start function (10s).
- 2 . Battery autofix feature.
- 3 . LCD screen display (Charging time , Temperature , Charging current / voltage , Battery capacity.
- 4 . Adjustable charging current 4A / 8A / 12A / 20A / 30A / 40A.
- 5 . Reverse connecting protection.
- 6 . Three phase charging mode.
- 7 . OEM & ODM are acceptable.



Technical Parameter

MH-series

Model	MH-1210A	MH-1220A	MH-1230A	MH-1240A
Input Voltage	150V/250V	180V/240V	180V/240V	180V/240V
Apply to the battery voltage (DC)	12V	12V	12V	12V
Maximum charge voltage	14.5V	14.5V	14.5V	14.5V
Maximum Charger Current	10A	20A	30A	40A
Display method	Digital	Digital	Digital	Digital
AC Input Frequency	47~63HZ	47~63HZ	47~63HZ	47~63HZ
Charging mode	Three-phase	Three-phase	Three-phase	Three-phase
Full load efficiency	>90%	>90%	>90%	>90%
Packed QTY/CTN	20PCS	16PCS	20PCS	20PCS
Certification	ISO,CTA,CE			